



EW-IP6040BVF

With features of simple installation, easy operation, and high performance-cost ratio, This Series camera is applicable to small and medium-sized scenes, such as homes/residences, small-sized retail stores, and other small and medium-sized enterprises. This product uses the latest PoE technology to troubleshoot the occurrence of any issues in the system making it easier to use. With the help of this technology, your camera now only consumes energy directly from the power supply and doesn't require any mid-way switches. Regions of Interest (ROI) is a user defined feature that allows the operator to monitor specific areas of a scene while still maintaining overall situational awareness of less important areas

Key Features-



- ❖ 1/1.8" Progressive Scan CMOS
- ❖ 3328 × 1872 @ 20/30 fps, Support Up to 3072 × 1728 @ 30 fps
- ❖ 4.4~9.3MM Motorized Varifocal Lens
- ❖ Color: 0.04 Lux @ (F2.0, AGC ON)
- ❖ H.265, H.265+, H.264, H.264+
- ❖ 120 dB WDR
- ❖ 3D DNR
- ❖ IR Range up to 40 Meter

Specification

Camera	Image Sensor:	1/1.8" Progressive Scan CMOS Image Sensor
	Scanning System:	Progressive
	Min. Illumination:	Color: 0.04 Lux @ (F2.0, AGC On) B/W: 0.004 Lux @ (F2.0, AGC On) 0 Lux with IR On
	Effective Pixels:	3328(H) x 1872(V)
	Shutter Time:	2s – 1/12000 sec
	Shutter Type:	Auto/Manual
	Slow Shutter:	Yes
	Output:	PAL/NTSC Adjustable
	DNR:	SSNR V, Wise NR II, 3D DNR
	RAM/ROM:	4GB/512MB
	Max. Image Resolution:	6 Mega Pixel (3328x1872) @ 25fps/30fps

	<table border="1"> <tr> <td>Day& Night:</td> <td>Day, Night, Auto, Schedule, IR Cut Filter</td> </tr> <tr> <td>WDR:</td> <td>120db True WDR</td> </tr> <tr> <td>BLC/AGC/SI:</td> <td>Auto/Manual</td> </tr> <tr> <td>Auto Gain Control:</td> <td>Auto/Manual</td> </tr> <tr> <td>S/N Ratio:</td> <td>>65db</td> </tr> <tr> <td>White Balance:</td> <td>Auto/Manual/Natural/Street Lamp/Outdoor/Regional</td> </tr> <tr> <td>Angle Adjustment:</td> <td>Pan: 0° to 0°~360°, tilt: -0° to 90°, rotate: 0° to 360°</td> </tr> </table>	Day& Night:	Day, Night, Auto, Schedule, IR Cut Filter	WDR:	120db True WDR	BLC/AGC/SI:	Auto/Manual	Auto Gain Control:	Auto/Manual	S/N Ratio:	>65db	White Balance:	Auto/Manual/Natural/Street Lamp/Outdoor/Regional	Angle Adjustment:	Pan: 0° to 0°~360°, tilt: -0° to 90°, rotate: 0° to 360°				
Day& Night:	Day, Night, Auto, Schedule, IR Cut Filter																		
WDR:	120db True WDR																		
BLC/AGC/SI:	Auto/Manual																		
Auto Gain Control:	Auto/Manual																		
S/N Ratio:	>65db																		
White Balance:	Auto/Manual/Natural/Street Lamp/Outdoor/Regional																		
Angle Adjustment:	Pan: 0° to 0°~360°, tilt: -0° to 90°, rotate: 0° to 360°																		
Camera Lens	<table border="1"> <tr> <td>Focal Length:</td> <td>4.4~9.3 MM Motorized Varifocal Lens</td> </tr> <tr> <td>Lens Type:</td> <td>P-IRIS Motorized Varifocal Lens</td> </tr> <tr> <td>Mount Type:</td> <td>M12</td> </tr> <tr> <td>Max Aperture:</td> <td>F1.3(Wide)~F2.15(Tele)</td> </tr> <tr> <td>IRIS Control Type:</td> <td>P-IRIS Auto</td> </tr> <tr> <td>Field of View:</td> <td>Horizontal: 113°(Wide) - 47°(Tele) Vertical: 58°(Wide) - 26°(Tele) Diagonal: 138°(Wide) - 54°(Tele)</td> </tr> <tr> <td>Focus:</td> <td>Auto, Semi-Auto, Manual</td> </tr> <tr> <td>Digital Zoom:</td> <td>16X</td> </tr> <tr> <td>Close Focus Distance:</td> <td>0.5M (1.64 Feet)</td> </tr> </table>	Focal Length:	4.4~9.3 MM Motorized Varifocal Lens	Lens Type:	P-IRIS Motorized Varifocal Lens	Mount Type:	M12	Max Aperture:	F1.3(Wide)~F2.15(Tele)	IRIS Control Type:	P-IRIS Auto	Field of View:	Horizontal: 113°(Wide) - 47°(Tele) Vertical: 58°(Wide) - 26°(Tele) Diagonal: 138°(Wide) - 54°(Tele)	Focus:	Auto, Semi-Auto, Manual	Digital Zoom:	16X	Close Focus Distance:	0.5M (1.64 Feet)
Focal Length:	4.4~9.3 MM Motorized Varifocal Lens																		
Lens Type:	P-IRIS Motorized Varifocal Lens																		
Mount Type:	M12																		
Max Aperture:	F1.3(Wide)~F2.15(Tele)																		
IRIS Control Type:	P-IRIS Auto																		
Field of View:	Horizontal: 113°(Wide) - 47°(Tele) Vertical: 58°(Wide) - 26°(Tele) Diagonal: 138°(Wide) - 54°(Tele)																		
Focus:	Auto, Semi-Auto, Manual																		
Digital Zoom:	16X																		
Close Focus Distance:	0.5M (1.64 Feet)																		
IR	<table border="1"> <tr> <td>IR Range:</td> <td>Up to 40 Meter</td> </tr> <tr> <td>Wavelength:</td> <td>850nm</td> </tr> </table>	IR Range:	Up to 40 Meter	Wavelength:	850nm														
IR Range:	Up to 40 Meter																		
Wavelength:	850nm																		
Sharpness	<table border="1"> <tr> <td>HLC:</td> <td>50Hz:25fps CIF (352×288) 60Hz:30fps CIF (352×240)</td> </tr> <tr> <td>BLC:</td> <td>Support</td> </tr> <tr> <td>OSD:</td> <td>8 OSD</td> </tr> <tr> <td>ROI:</td> <td>8 Area</td> </tr> <tr> <td>Defog:</td> <td>Support</td> </tr> </table>	HLC:	50Hz:25fps CIF (352×288) 60Hz:30fps CIF (352×240)	BLC:	Support	OSD:	8 OSD	ROI:	8 Area	Defog:	Support								
HLC:	50Hz:25fps CIF (352×288) 60Hz:30fps CIF (352×240)																		
BLC:	Support																		
OSD:	8 OSD																		
ROI:	8 Area																		
Defog:	Support																		
Compression	<table border="1"> <tr> <td>Video Compression:</td> <td>Main Stream: H.265/H.264/H.264+/H.265+ Sub-Stream: H.265/H.264/MJPEG Third Stream: H.265/H.264 Fourth Stream: H.265/H.264/MJPEG</td> </tr> <tr> <td>H.264 Type:</td> <td>Baseline Profile/Main Profile/High Profile</td> </tr> <tr> <td>Video Bit Rate:</td> <td>128Kbps~8Mbps</td> </tr> <tr> <td>Bit Rate Control:</td> <td>CBR/VBR</td> </tr> </table>	Video Compression:	Main Stream: H.265/H.264/H.264+/H.265+ Sub-Stream: H.265/H.264/MJPEG Third Stream: H.265/H.264 Fourth Stream: H.265/H.264/MJPEG	H.264 Type:	Baseline Profile/Main Profile/High Profile	Video Bit Rate:	128Kbps~8Mbps	Bit Rate Control:	CBR/VBR										
Video Compression:	Main Stream: H.265/H.264/H.264+/H.265+ Sub-Stream: H.265/H.264/MJPEG Third Stream: H.265/H.264 Fourth Stream: H.265/H.264/MJPEG																		
H.264 Type:	Baseline Profile/Main Profile/High Profile																		
Video Bit Rate:	128Kbps~8Mbps																		
Bit Rate Control:	CBR/VBR																		
Image	<table border="1"> <tr> <td>Resolution:</td> <td>3318x1872, 3072x1728, 2592x1944, 2688x1520, 1920x1080, 1600x1200, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240</td> </tr> </table>	Resolution:	3318x1872, 3072x1728, 2592x1944, 2688x1520, 1920x1080, 1600x1200, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240																
Resolution:	3318x1872, 3072x1728, 2592x1944, 2688x1520, 1920x1080, 1600x1200, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240																		

	<table border="1"> <tr> <td data-bbox="391 107 792 191">Max Frame Rate:</td> <td data-bbox="792 107 1490 191">H.264/H.265: Max 30fps/25fps(60/50Hz) MJPEG: Max 30fps @ 6MP Max.25fps</td> </tr> <tr> <td data-bbox="391 191 792 338">Streaming:</td> <td data-bbox="792 191 1490 338">Main Stream: 6MP (3318x1872), 5MP (2592x1944), 4MP (2560x1440), 1080P (1920x1080), 720P (1280x720) D1, CIF 480x240, Max 30fps Sub Stream 1: 704 x 576; 25 FPS PAL/ 30 FPS NTSC,</td> </tr> <tr> <td data-bbox="391 338 792 390">Image Enhancement:</td> <td data-bbox="792 338 1490 390">BLC, HLC, 3D DNR, Defog, EIS, ROI, AWB, AGC</td> </tr> <tr> <td data-bbox="391 390 792 474">Video Analytics:</td> <td data-bbox="792 390 1490 474">Trip Wire, Perimeter, Video Motion Detection, Tampering, Loitering, Intrusion & People Counting</td> </tr> <tr> <td data-bbox="391 474 792 527">Video Parameters:</td> <td data-bbox="792 474 1490 527">Backlight Compensation BLC, WDR, SSSR, ICR Setting</td> </tr> <tr> <td data-bbox="391 527 792 642">Image Setting:</td> <td data-bbox="792 527 1490 642">Rotate Mode, Saturation, Brightness, Contrast, Sharpness, AGC, white balance adjustable by client software or web browser</td> </tr> <tr> <td data-bbox="391 642 792 695">Target Cropping:</td> <td data-bbox="792 642 1490 695">Yes</td> </tr> <tr> <td data-bbox="391 695 792 747">SVC:</td> <td data-bbox="792 695 1490 747">H.264 and H.265 Encoding</td> </tr> </table>	Max Frame Rate:	H.264/H.265: Max 30fps/25fps(60/50Hz) MJPEG: Max 30fps @ 6MP Max.25fps	Streaming:	Main Stream: 6MP (3318x1872), 5MP (2592x1944), 4MP (2560x1440), 1080P (1920x1080), 720P (1280x720) D1, CIF 480x240, Max 30fps Sub Stream 1: 704 x 576; 25 FPS PAL/ 30 FPS NTSC,	Image Enhancement:	BLC, HLC, 3D DNR, Defog, EIS, ROI, AWB, AGC	Video Analytics:	Trip Wire, Perimeter, Video Motion Detection, Tampering, Loitering, Intrusion & People Counting	Video Parameters:	Backlight Compensation BLC, WDR, SSSR, ICR Setting	Image Setting:	Rotate Mode, Saturation, Brightness, Contrast, Sharpness, AGC, white balance adjustable by client software or web browser	Target Cropping:	Yes	SVC:	H.264 and H.265 Encoding						
Max Frame Rate:	H.264/H.265: Max 30fps/25fps(60/50Hz) MJPEG: Max 30fps @ 6MP Max.25fps																						
Streaming:	Main Stream: 6MP (3318x1872), 5MP (2592x1944), 4MP (2560x1440), 1080P (1920x1080), 720P (1280x720) D1, CIF 480x240, Max 30fps Sub Stream 1: 704 x 576; 25 FPS PAL/ 30 FPS NTSC,																						
Image Enhancement:	BLC, HLC, 3D DNR, Defog, EIS, ROI, AWB, AGC																						
Video Analytics:	Trip Wire, Perimeter, Video Motion Detection, Tampering, Loitering, Intrusion & People Counting																						
Video Parameters:	Backlight Compensation BLC, WDR, SSSR, ICR Setting																						
Image Setting:	Rotate Mode, Saturation, Brightness, Contrast, Sharpness, AGC, white balance adjustable by client software or web browser																						
Target Cropping:	Yes																						
SVC:	H.264 and H.265 Encoding																						
Audio	<table border="1"> <tr> <td data-bbox="391 764 792 827">Audio Compression:</td> <td data-bbox="792 764 1490 827">G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/AAC</td> </tr> <tr> <td data-bbox="391 827 792 879">Audio Bit Rate:</td> <td data-bbox="792 827 1490 879">8-320Kbps (MP3)</td> </tr> <tr> <td data-bbox="391 879 792 932">Built-in Mic</td> <td data-bbox="792 879 1490 932">Yes</td> </tr> <tr> <td data-bbox="391 932 792 984">Environmental Noise Filtering:</td> <td data-bbox="792 932 1490 984">Yes</td> </tr> <tr> <td data-bbox="391 984 792 1037">Audio Sampling Rate:</td> <td data-bbox="792 984 1490 1037">8 kHz/16 kHz/32 kHz/44.1 kHz/48 kHz</td> </tr> </table>	Audio Compression:	G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/AAC	Audio Bit Rate:	8-320Kbps (MP3)	Built-in Mic	Yes	Environmental Noise Filtering:	Yes	Audio Sampling Rate:	8 kHz/16 kHz/32 kHz/44.1 kHz/48 kHz												
Audio Compression:	G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/AAC																						
Audio Bit Rate:	8-320Kbps (MP3)																						
Built-in Mic	Yes																						
Environmental Noise Filtering:	Yes																						
Audio Sampling Rate:	8 kHz/16 kHz/32 kHz/44.1 kHz/48 kHz																						
Network	<table border="1"> <tr> <td data-bbox="391 1052 792 1167">Alarm Trigger:</td> <td data-bbox="792 1052 1490 1167">Motion detection, video tampering alarm, exception (network disconnected, IP address conflict, illegal login, HDD full, HDD error)</td> </tr> <tr> <td data-bbox="391 1167 792 1283">Smart Event:</td> <td data-bbox="792 1167 1490 1283">Unattended baggage detection, object removal detection, scene change detection, audio exception detection, video quality diagnosis</td> </tr> <tr> <td data-bbox="391 1283 792 1335">Linkage:</td> <td data-bbox="792 1283 1490 1335">trigger capture</td> </tr> <tr> <td data-bbox="391 1335 792 1482">Protocols:</td> <td data-bbox="792 1335 1490 1482">TCP/IP, IPv4, ICMP, HTTP, HTTPS, HTTP-Base64, HTTP-Digest, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, FTP, RTMP, IGMP, 802.1X, QoS, Multicast</td> </tr> <tr> <td data-bbox="391 1482 792 1535">Simultaneous View:</td> <td data-bbox="792 1482 1490 1535">Up To 12 Channels</td> </tr> <tr> <td data-bbox="391 1535 792 1587">Users:</td> <td data-bbox="792 1535 1490 1587">Up to 32 users. 3 levels: administrator, operator and user</td> </tr> <tr> <td data-bbox="391 1587 792 1640">API:</td> <td data-bbox="792 1587 1490 1640">Open Network Video Interface, ISAPI</td> </tr> <tr> <td data-bbox="391 1640 792 1692">Privacy Masking:</td> <td data-bbox="792 1640 1490 1692">8 Areas</td> </tr> <tr> <td data-bbox="391 1692 792 1745">Motion Detection:</td> <td data-bbox="792 1692 1490 1745">ON/Off</td> </tr> <tr> <td data-bbox="391 1745 792 1797">Mobile:</td> <td data-bbox="792 1745 1490 1797">iPhone, iPad, Android</td> </tr> <tr> <td data-bbox="391 1797 792 1944">Security Measures:</td> <td data-bbox="792 1797 1490 1944">Password Protection, HTTPS Encryption, IEEE 802.1x port-Based Network Access Control, IP Address Filter, Basic and Digest Authentication for HTTP/HTTPS, WSSE and Digest Authentication for ONVIF</td> </tr> </table>	Alarm Trigger:	Motion detection, video tampering alarm, exception (network disconnected, IP address conflict, illegal login, HDD full, HDD error)	Smart Event:	Unattended baggage detection, object removal detection, scene change detection, audio exception detection, video quality diagnosis	Linkage:	trigger capture	Protocols:	TCP/IP, IPv4, ICMP, HTTP, HTTPS, HTTP-Base64, HTTP-Digest, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, FTP, RTMP, IGMP, 802.1X, QoS, Multicast	Simultaneous View:	Up To 12 Channels	Users:	Up to 32 users. 3 levels: administrator, operator and user	API:	Open Network Video Interface, ISAPI	Privacy Masking:	8 Areas	Motion Detection:	ON/Off	Mobile:	iPhone, iPad, Android	Security Measures:	Password Protection, HTTPS Encryption, IEEE 802.1x port-Based Network Access Control, IP Address Filter, Basic and Digest Authentication for HTTP/HTTPS, WSSE and Digest Authentication for ONVIF
Alarm Trigger:	Motion detection, video tampering alarm, exception (network disconnected, IP address conflict, illegal login, HDD full, HDD error)																						
Smart Event:	Unattended baggage detection, object removal detection, scene change detection, audio exception detection, video quality diagnosis																						
Linkage:	trigger capture																						
Protocols:	TCP/IP, IPv4, ICMP, HTTP, HTTPS, HTTP-Base64, HTTP-Digest, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, FTP, RTMP, IGMP, 802.1X, QoS, Multicast																						
Simultaneous View:	Up To 12 Channels																						
Users:	Up to 32 users. 3 levels: administrator, operator and user																						
API:	Open Network Video Interface, ISAPI																						
Privacy Masking:	8 Areas																						
Motion Detection:	ON/Off																						
Mobile:	iPhone, iPad, Android																						
Security Measures:	Password Protection, HTTPS Encryption, IEEE 802.1x port-Based Network Access Control, IP Address Filter, Basic and Digest Authentication for HTTP/HTTPS, WSSE and Digest Authentication for ONVIF																						

	<table border="1"> <tr> <td>Compatible Integration:</td> <td>ONVIF (Profile S/G/T), API</td> </tr> <tr> <td>Mirror:</td> <td>Yes</td> </tr> <tr> <td>Encrypted Data Transmission:</td> <td>HTTPS (SSL/TSL)</td> </tr> <tr> <td>Web Browser:</td> <td>Plug-in required live view: IE 10+ Plug-in free live view: Chrome 57.0+, Firefox 52.0+ Local service: Chrome 57.0+, Firefox 52.0+</td> </tr> <tr> <td>General Function:</td> <td>One-key Reset, Anti-Flicker, 5 Streams and up to 5 Custom Streams, Heartbeat, Password Protection, Privacy Mask, Watermark, IP Address Filter</td> </tr> </table>	Compatible Integration:	ONVIF (Profile S/G/T), API	Mirror:	Yes	Encrypted Data Transmission:	HTTPS (SSL/TSL)	Web Browser:	Plug-in required live view: IE 10+ Plug-in free live view: Chrome 57.0+, Firefox 52.0+ Local service: Chrome 57.0+, Firefox 52.0+	General Function:	One-key Reset, Anti-Flicker, 5 Streams and up to 5 Custom Streams, Heartbeat, Password Protection, Privacy Mask, Watermark, IP Address Filter				
Compatible Integration:	ONVIF (Profile S/G/T), API														
Mirror:	Yes														
Encrypted Data Transmission:	HTTPS (SSL/TSL)														
Web Browser:	Plug-in required live view: IE 10+ Plug-in free live view: Chrome 57.0+, Firefox 52.0+ Local service: Chrome 57.0+, Firefox 52.0+														
General Function:	One-key Reset, Anti-Flicker, 5 Streams and up to 5 Custom Streams, Heartbeat, Password Protection, Privacy Mask, Watermark, IP Address Filter														
Interface	<table border="1"> <tr> <td>Communication Interface:</td> <td>1 RJ45 10M / 100M Ethernet Interface Port</td> </tr> <tr> <td>Audio:</td> <td>1 Input, 1 Output, Mono Sound</td> </tr> <tr> <td>Alarm:</td> <td>2 Input, 2 Output</td> </tr> <tr> <td>Video Output:</td> <td>1Vp-p composite output (75 Ω/ CVBS)</td> </tr> <tr> <td>Video Out USB:</td> <td>Micro USB Type B</td> </tr> <tr> <td>On Board Storage:</td> <td>Support SD/Micro SD Card Up to 512GB, NAS</td> </tr> <tr> <td>Reset Button:</td> <td>Yes</td> </tr> </table>	Communication Interface:	1 RJ45 10M / 100M Ethernet Interface Port	Audio:	1 Input, 1 Output, Mono Sound	Alarm:	2 Input, 2 Output	Video Output:	1Vp-p composite output (75 Ω/ CVBS)	Video Out USB:	Micro USB Type B	On Board Storage:	Support SD/Micro SD Card Up to 512GB, NAS	Reset Button:	Yes
Communication Interface:	1 RJ45 10M / 100M Ethernet Interface Port														
Audio:	1 Input, 1 Output, Mono Sound														
Alarm:	2 Input, 2 Output														
Video Output:	1Vp-p composite output (75 Ω/ CVBS)														
Video Out USB:	Micro USB Type B														
On Board Storage:	Support SD/Micro SD Card Up to 512GB, NAS														
Reset Button:	Yes														
Smart Features	<table border="1"> <tr> <td>Cyber Security:</td> <td>Video Encryption, Configuration Encryption, Digest, WSSE, Account Lock, Security Logs, Generation</td> </tr> <tr> <td>Smart Analytics Features:</td> <td>Line Crossing Detection, Intrusion Detection, Region Entrance Detection, Region Exiting Detection, Unattended Baggage Detection, Object Removal detection</td> </tr> <tr> <td>Exception Detection:</td> <td>Scene Change Detection, Defocus Detection</td> </tr> <tr> <td>Statistics:</td> <td>Counting</td> </tr> <tr> <td>Face Detection:</td> <td>Yes</td> </tr> <tr> <td>Smart Detection:</td> <td>Tripwire, Intrusion</td> </tr> <tr> <td>Region of Interest:</td> <td>Main Stream/Sub Stream/Third Stream/Fourth Stream/Fifth Stream: 4 Fixed Regions For Each Stream And Dynamic Face Tracking</td> </tr> </table>	Cyber Security:	Video Encryption, Configuration Encryption, Digest, WSSE, Account Lock, Security Logs, Generation	Smart Analytics Features:	Line Crossing Detection, Intrusion Detection, Region Entrance Detection, Region Exiting Detection, Unattended Baggage Detection, Object Removal detection	Exception Detection:	Scene Change Detection, Defocus Detection	Statistics:	Counting	Face Detection:	Yes	Smart Detection:	Tripwire, Intrusion	Region of Interest:	Main Stream/Sub Stream/Third Stream/Fourth Stream/Fifth Stream: 4 Fixed Regions For Each Stream And Dynamic Face Tracking
Cyber Security:	Video Encryption, Configuration Encryption, Digest, WSSE, Account Lock, Security Logs, Generation														
Smart Analytics Features:	Line Crossing Detection, Intrusion Detection, Region Entrance Detection, Region Exiting Detection, Unattended Baggage Detection, Object Removal detection														
Exception Detection:	Scene Change Detection, Defocus Detection														
Statistics:	Counting														
Face Detection:	Yes														
Smart Detection:	Tripwire, Intrusion														
Region of Interest:	Main Stream/Sub Stream/Third Stream/Fourth Stream/Fifth Stream: 4 Fixed Regions For Each Stream And Dynamic Face Tracking														
General	<table border="1"> <tr> <td>Language:</td> <td>English, Russian, Estonian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenian, Serbian, Turkish, Korean, Traditional Chinese, Thai, Vietnamese, Japanese, Latvian, Lithuanian, Portuguese (Brazil), Ukrainian</td> </tr> <tr> <td>Operating Conditions:</td> <td>-40 °C ~ 70 °C (-40 °F ~ 140 °F) Humidity 95% or less (non-condensing)</td> </tr> <tr> <td>Power Supply:</td> <td>12 VDC ± 25%, 0.55 A, max. 6.5 W, Ø5.5 mm coaxial power plug PoE: 802.3af, Class 3, 36 V to 57 V, 0.24 A to 0.14 A, max. 8.5 W</td> </tr> <tr> <td>Power Consumption:</td> <td>12 VDC, 1.2A, MAX 13.2 W</td> </tr> </table>	Language:	English, Russian, Estonian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenian, Serbian, Turkish, Korean, Traditional Chinese, Thai, Vietnamese, Japanese, Latvian, Lithuanian, Portuguese (Brazil), Ukrainian	Operating Conditions:	-40 °C ~ 70 °C (-40 °F ~ 140 °F) Humidity 95% or less (non-condensing)	Power Supply:	12 VDC ± 25%, 0.55 A, max. 6.5 W, Ø5.5 mm coaxial power plug PoE: 802.3af, Class 3, 36 V to 57 V, 0.24 A to 0.14 A, max. 8.5 W	Power Consumption:	12 VDC, 1.2A, MAX 13.2 W						
Language:	English, Russian, Estonian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenian, Serbian, Turkish, Korean, Traditional Chinese, Thai, Vietnamese, Japanese, Latvian, Lithuanian, Portuguese (Brazil), Ukrainian														
Operating Conditions:	-40 °C ~ 70 °C (-40 °F ~ 140 °F) Humidity 95% or less (non-condensing)														
Power Supply:	12 VDC ± 25%, 0.55 A, max. 6.5 W, Ø5.5 mm coaxial power plug PoE: 802.3af, Class 3, 36 V to 57 V, 0.24 A to 0.14 A, max. 8.5 W														
Power Consumption:	12 VDC, 1.2A, MAX 13.2 W														

	Weather Proof:	IP 67 IK10
	Weight:	350g
	Casing:	Metal/Plastic
	Certification:	BIS, CE, FC, ROHS
	Country of Origin:	India