



EW-24PWMPOE1GSFP4

Specification

Type of Switch	Web Managed
Technology	PoE+
Number of 1G Copper Ports	24
Number of 10G Copper Ports	0
Number of 1 G SFP Port (Uplink)	4
Number of 10 G SFP+ Port (Uplink)	0
Multi-Gigabit Support	No
Redundant Power supply (from day one)	Not Available
Console Port	Available
Switching Capacity-Non Blocking (Gbps)	56

Throughput (MPPS)	41.7
Operating System	Available
Dedicated Stacking Port/Slot (from day one)	Not Available
Stacking Bandwidth (Gbps)	0
Basic Layer-3 Protocol	64 IPv4 static routes - 32 IPv6 static routes , 4 IP interfaces , Max. 256 ARP entries
Security Feature	SSH v2 • SSL v1/2/3 • Port security , ARP inspection - IP inspection - IPv6 DHCP snooping
Management Protocol	SNMP v1/v2c/v3 , RMON v1 • RMON v2 • LLDP , CPU monitoring • Sntp • LLDP-MED , FULL CLI
QoS	Queue handling - Strict priority - Weighted Round Robin WRR • 8 outbound queues , Bandwidth control
Operating Temperature Range (Degree C)	-5 - 50°C
Operating Humidity (RH)(%)	0% - 95% RH
IPv6 Ready from day one and dully certified	Yes
PoE Power Budget (Watt)	193
On Site OEM Warranty	1 Year