



## EW-8PMPOE10GSFP2

### HARDWARE FEATURES

Interface	<ul style="list-style-type: none"><li>• 8× 100/1000/2500 Mbps RJ45 Ports</li><li>• 2× 10G SFP+ Slots</li><li>• 1× RJ45 Console Port</li><li>• 1× Micro-USB Console Port</li></ul>
Fan Quantity	2
Power Supply	100-240 V AC~50/60 Hz
PoE+ Ports(RJ45)	<ul style="list-style-type: none"><li>• Standard: 802.3at/af compliant</li><li>• PoE+ Ports: 8 Ports</li><li>• PoE Power Budget: 240 W*</li></ul>
Mounting	Rack Mountable
Max Power Consumption	285.9 W (110V/60Hz) (with 240 W PD connected)
Max Heat Dissipation	975.54 BTU/hr (110V/60Hz) (with 240 W PD connected)

### PERFORMANCE

Switching Capacity	80 Gbps
Packet Forwarding Rate	59.52 Mpps



MAC Address Table	16 K
Packet Buffer Memory	12 Mbit
Jumbo Frame	9 KB

### SOFTWARE FEATURES

Quality of Service	<ul style="list-style-type: none"><li>• 8 priority queues</li><li>• 802.1p CoS/DSCP priority</li><li>• Queue scheduling<ul style="list-style-type: none"><li>- SP (Strict Priority)</li><li>- WRR (Weighted Round Robin)</li><li>- SP+WRR</li></ul></li><li>• Bandwidth Control<ul style="list-style-type: none"><li>- Port/Flow based Rating Limiting</li></ul></li><li>• Smoother Performance</li><li>• Action for Flows<ul style="list-style-type: none"><li>- Mirror (to supported interface)</li><li>- Redirect (to supported interface)</li><li>- Rate Limit</li><li>- QoS Remark</li></ul></li></ul>
L3 Features	<ul style="list-style-type: none"><li>• 16 IPv4/IPv6 Interfaces</li><li>• Static Routing<ul style="list-style-type: none"><li>- 48 static routes</li></ul></li><li>• Static ARP<ul style="list-style-type: none"><li>- 128 Static Entries</li></ul></li><li>• Proxy ARP</li><li>• Gratuitous ARP</li><li>• DHCP Server</li><li>• DHCP Relay<ul style="list-style-type: none"><li>- DHCP Interface Relay</li><li>- DHCP VLAN Relay</li></ul></li><li>• DHCP L2 Relay</li></ul>
L2 and L2+ Features	<ul style="list-style-type: none"><li>• Link Aggregation<ul style="list-style-type: none"><li>- static link aggregation</li><li>- 802.3ad LACP</li><li>- Up to 8 aggregation groups, containing 8 ports per group</li></ul></li><li>• Spanning Tree Protocol</li></ul>

	<ul style="list-style-type: none"> <li>- 802.1d STP</li> <li>- 802.1w RSTP</li> <li>- 802.1s MSTP</li> <li>- STP Security: TC Protect, BPDU Filter, Root Protect</li> <li>• Loopback Detection</li> <li>- Port based</li> <li>- VLAN based</li> <li>• Flow Control</li> <li>- 802.3x Flow Control</li> <li>- HOL Blocking Prevention</li> <li>• Mirroring</li> <li>- Port Mirroring</li> <li>- CPU Mirroring</li> <li>- One-to-One</li> <li>- Many-to-One</li> <li>- Tx/Rx/Both</li> </ul>
L2 Multicast	<ul style="list-style-type: none"> <li>• IGMP Snooping</li> <li>- IGMP v1/v2/v3 Snooping</li> <li>- Fast Leave</li> <li>- IGMP Snooping Querier</li> <li>- IGMP Authentication</li> <li>• IGMP Authentication</li> <li>• MLD Snooping</li> <li>- MLD v1/v2 Snooping</li> <li>- Fast Leave</li> <li>- MLD Snooping Querier</li> <li>- Static Group Config</li> <li>- Limited IP Multicast</li> <li>• MVR</li> <li>• Multicast Filtering: 256 profiles and 16 entries per profile</li> </ul>
Advanced Features	<ul style="list-style-type: none"> <li>• Automatic Device Discovery</li> <li>• Batch Configuration</li> <li>• Batch Firmware Upgrading</li> <li>• Intelligent Network Monitoring</li> <li>• Abnormal Event Warnings</li> <li>• Unified Configuration</li> <li>• Reboot Schedule</li> </ul>
VLAN	<ul style="list-style-type: none"> <li>• VLAN Group</li> <li>- Max 4K VLAN Groups</li> <li>• 802.1Q Tagged VLAN</li> <li>• MAC VLAN: 7 Entries</li> </ul>

	<ul style="list-style-type: none"> <li>• Protocol VLAN: Protocol Template 16, Protocol VLAN 16</li> <li>• Private VLAN</li> <li>• GVRP</li> <li>• VLAN VPN (QinQ)             <ul style="list-style-type: none"> <li>- Port-Based QinQ</li> <li>- Selective QinQ</li> </ul> </li> <li>• Voice VLAN</li> </ul>
<p>Access Control List</p>	<ul style="list-style-type: none"> <li>• Time-based ACL</li> <li>• MAC ACL             <ul style="list-style-type: none"> <li>- Source MAC</li> <li>- Destination MAC</li> <li>- VLAN ID</li> <li>- User Priority</li> <li>- Ether Type</li> </ul> </li> <li>• IP ACL             <ul style="list-style-type: none"> <li>-Source IP</li> <li>- Destination IP</li> <li>- Fragment</li> <li>- IP Protocol</li> <li>- TCP Flag</li> <li>- TCP/UDP Port</li> <li>- DSCP/IP TOS</li> <li>- User Priority</li> </ul> </li> <li>• Combined ACL</li> <li>• Packet Content ACL</li> <li>• IPv6 ACL</li> <li>• Policy             <ul style="list-style-type: none"> <li>- Mirroring</li> <li>- Redirect</li> <li>- Rate Limit</li> <li>- QoS Remark</li> </ul> </li> <li>• ACL apply to Port/VLAN</li> </ul>
<p>Security</p>	<ul style="list-style-type: none"> <li>• IP-MAC-Port Binding             <ul style="list-style-type: none"> <li>- 512 Entries</li> <li>- DHCP Snooping</li> <li>- ARP Inspection</li> <li>- IPv4 Source Guard: 100 Entries</li> </ul> </li> <li>• IPv6-MAC-Port Binding             <ul style="list-style-type: none"> <li>- 512 Entries</li> <li>- DHCPv6 Snooping</li> <li>- ND Detection</li> <li>- IPv6 Source Guard: 100 Entries</li> </ul> </li> </ul>

	<ul style="list-style-type: none"> <li>• DoS Defend</li> <li>• Static/Dynamic Port Security             <ul style="list-style-type: none"> <li>- Up to 64 MAC addresses per port</li> </ul> </li> <li>• Broadcast/Multicast/Unicast Storm Control             <ul style="list-style-type: none"> <li>- kbps/ratio control mode</li> </ul> </li> <li>• 802.1X             <ul style="list-style-type: none"> <li>- Port base authentication</li> <li>- Mac base authentication</li> <li>- VLAN Assignment</li> <li>- MAB</li> <li>- Guest VLAN</li> </ul> </li> <li>- Support Radius authentication and accountability</li> <li>• AAA (including TACACS+)</li> <li>• Port Isolation</li> <li>• Secure web management through HTTPS with SSLv3/TLS 1.2</li> <li>• Secure Command Line Interface (CLI) management with SSHv1/SSHv2</li> <li>• IP/Port/MAC based access control</li> </ul>
IPv6	<ul style="list-style-type: none"> <li>• IPv6 Dual IPv4/IPv6</li> <li>• Multicast Listener Discovery (MLD) Snooping</li> <li>• IPv6 ACL</li> <li>• IPv6 Interface</li> <li>• Static IPv6 Routing</li> <li>• IPv6 neighbor discovery (ND)</li> <li>• Path maximum transmission unit (MTU) discovery</li> <li>• Internet Control Message Protocol (ICMP) version 6</li> <li>• TCPv6/UDPv6</li> <li>• IPv6 applications             <ul style="list-style-type: none"> <li>- DHCPv6 Client</li> <li>- Ping6</li> <li>- Tracert6</li> <li>- Telnet (v6)</li> <li>- IPv6 SNMP</li> <li>- IPv6 SSH</li> <li>- IPv6 SSL</li> <li>- Http/Https</li> <li>- IPv6 TFTP</li> </ul> </li> </ul>
Management	<ul style="list-style-type: none"> <li>• Web-based GUI</li> <li>• Command Line Interface (CLI) through the console port, telnet</li> <li>• SNMP v1/v2c/v3             <ul style="list-style-type: none"> <li>- Trap/Inform</li> </ul> </li> </ul>

	<ul style="list-style-type: none"> <li>- RMON (1,2,3,9 groups)</li> <li>• SDM Template</li> <li>• DHCP/BOOTP Client</li> <li>• 802.1ab LLDP/LLDP-MED</li> <li>• DHCP AutoInstall</li> <li>• Dual Image, Dual Configuration</li> <li>• CPU Monitoring</li> <li>• Cable Diagnostics</li> <li>• EEE</li> <li>• Password Recovery</li> <li>• Sntp</li> <li>• System Log</li> </ul>
MIBs	<ul style="list-style-type: none"> <li>• MIB II (RFC1213)</li> <li>• Interface MIB (RFC2233)</li> <li>• Ethernet Interface MIB (RFC1643)</li> <li>• Bridge MIB (RFC1493)</li> <li>• P/Q-Bridge MIB (RFC2674)</li> <li>• RMON MIB (RFC2819)</li> <li>• RMON2 MIB (RFC2021)</li> <li>• Radius Accounting Client MIB (RFC2620)</li> <li>• Radius Authentication Client MIB (RFC2618)</li> <li>• Remote Ping, Traceroute MIB (RFC2925)</li> <li>• Support TP-Link private MIB</li> </ul>

## MANAGEMENT

Management Features	<ul style="list-style-type: none"> <li>• Web-based GUI</li> <li>• Command Line Interface (CLI) through the console port, telnet</li> <li>• SNMP v1/v2c/v3</li> <li>- Trap/Inform</li> <li>- RMON (1,2,3,9 groups)</li> <li>• SDM Template</li> <li>• DHCP/BOOTP Client</li> <li>• 802.1ab LLDP/LLDP-MED</li> <li>• DHCP AutoInstall</li> <li>• Dual Image, Dual Configuration</li> <li>• CPU Monitoring</li> <li>• Cable Diagnostics</li> <li>• EEE</li> <li>• Password Recovery</li> <li>• Sntp</li> </ul>
---------------------	---



	<ul style="list-style-type: none"><li>• System Log</li></ul>
--	--

**OTHERS**

Environment	<ul style="list-style-type: none"><li>• Operating Temperature: 0–50 °C (32–122 °F);</li><li>• Storage Temperature: -40–70 °C (-40–158 °F)</li><li>• Operating Humidity: 10–90% RH non-condensing</li><li>• Storage Humidity: 5–90% RH non-condensing</li></ul>
System Requirements	Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ or Windows 7/8/10/11, MAC® OS, NetWare®, UNIX® or Linux.
Certification	CE, FCC, RoHS, ISO

[www.ewit.in](http://www.ewit.in)