



## EW-8PMPOE1GSFP2

### HARDWARE FEATURES

Standards and Protocols	IEEE 802.3i, IEEE 802.3u, IEEE 802.3z, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3x, IEEE 802.1d, IEEE 802.1s, IEEE 802.1w, IEEE 802.1q, IEEE 802.1p, IEEE 802.1x
Interface	8 10/100/1000Mbps RJ45 Ports 2 1000Mbps SFP Slots (Auto-Negotiation/Auto MDI/MDIX)
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) 100BASE-TX/1000Base-T: UTP category 5, 5e or above cable (maximum 100m) 1000BASE-X: MMF, SMF
Fan Quantity	Fanless
Power Supply	100~240VAC, 50/60Hz External Power Adapter(Output: 54VDC/1.3A)
Power Consumption	<ul style="list-style-type: none"> <li>• 10.3W (without POE device connected)</li> <li>• 76.5W (with 61W POE devices connected)</li> </ul>



PoE Ports (RJ45)	<ul style="list-style-type: none"><li>• Standard: 802.3af/at compliant</li><li>• PoE Ports: 8 Ports</li><li>• Power Supply: 61 W*</li></ul>
Mounting	Desktop / Wall-Mounting
Max Power Consumption	<ul style="list-style-type: none"><li>• V3.2: 76.5 W (220 V/50 Hz) (with 61 W PD connected); 10.3 W (220 V/50 Hz) (no PD connected)</li><li>• V4: 74.4 W (220 V/50 Hz) (with 61 W PD connected)</li><li>• V5: 77.8 W (110 V/60 Hz) (with 61 W PD connected)</li></ul>
Max Heat Dissipation	<ul style="list-style-type: none"><li>• V3.2: 261.02 BTU/hr (220 V/50 Hz) (with 61 W PD connected); 35.14 BTU/hr (220 V/50 Hz) (no PD connected)</li><li>• V4: 253.89 BTU/hr (220 V/50 Hz) (with 61 W PD connected)</li><li>• V5: 265.3 BTU/hr (110 V/60 Hz) (with 61 W PD connected)</li></ul>

## PERFORMANCE

Switching Capacity	20 Gbps
Bandwidth/Backplane	20 Gbps
Packet Forwarding Rate	14.88 Mpps
MAC Address Table	8K
Packet Buffer Memory	4.1 Mbit
Jumbo Frame	9 KB

## SOFTWARE FEATURES

Quality of Service	<ul style="list-style-type: none"><li>• 802.1p CoS/DSCP priority</li><li>• 8 priority queues</li><li>• Priority Schedule Mode</li><li>- SP (Strict Priority)</li></ul>
--------------------	--

	<ul style="list-style-type: none"> <li>- WRR (Weighted Round Robin)             <ul style="list-style-type: none"> <li>• Queue Weight Config</li> <li>• Bandwidth Control</li> </ul> </li> <li>- Port/Flow based Rating Limit             <ul style="list-style-type: none"> <li>• Smoother Performance</li> <li>• Storm Control</li> </ul> </li> <li>- Multiple Control Modes(kbps/ratio)</li> <li>- Broadcast/Multicast/Unknown-Unicast Control</li> </ul>
<p>L2 and L2+ Features</p>	<ul style="list-style-type: none"> <li>• 16 IP Interfaces</li> <li>- Support IPv4/IPv6 Interface             <ul style="list-style-type: none"> <li>• Static Routing</li> <li>- 32 IPv4/IPv6 Static Routes</li> </ul> </li> <li>• DHCP Server</li> <li>• DHCP Relay</li> <li>- DHCP Interface Relay</li> <li>- DHCP VLAN Relay</li> <li>• DHCP L2 Relay</li> <li>• Static ARP</li> <li>• Proxy ARP</li> <li>• Gratuitous ARP</li> <li>• Link Aggregation             <ul style="list-style-type: none"> <li>- Static link aggregation</li> <li>- 802.3ad LACP</li> <li>- Up to 8 aggregation groups and up to 8 ports per group</li> </ul> </li> <li>• Spanning Tree Protocol             <ul style="list-style-type: none"> <li>- 802.1D STP</li> <li>- 802.1w RSTP</li> <li>- 802.1s MSTP</li> <li>- STP Security: TC Protect, BPDU Filter/Protect, Root Protect</li> </ul> </li> <li>• Loopback Detection</li> <li>• Flow Control             <ul style="list-style-type: none"> <li>- 802.3x Flow Control</li> </ul> </li> <li>• Mirroring             <ul style="list-style-type: none"> <li>- Port Mirroring</li> <li>- CPU Mirroring</li> <li>- One-to-One</li> <li>- Many-to-One</li> <li>- Flow-Based</li> <li>- Ingress/Egress/Both</li> </ul> </li> <li>• Device Link Detect Protocol (DLDP)</li> <li>• 802.1ab LLDP/ LLDP-MED</li> </ul>

<p>L2 Multicast</p>	<ul style="list-style-type: none"> <li>• 511 IPv4, IPv6 shared multicast groups</li> <li>• IGMP Snooping             <ul style="list-style-type: none"> <li>- IGMP v1/v2/v3 Snooping</li> <li>- Fast Leave</li> <li>- IGMP Snooping Querier</li> <li>- Static Group Config</li> </ul> </li> <li>• Multicast VLAN Registration (MVR)</li> <li>• Multicast Filtering</li> <li>• MLD Snooping             <ul style="list-style-type: none"> <li>- MLD v1/v2 Snooping</li> <li>- Fast Leave</li> <li>- MLD Snooping Querier</li> <li>- Static Group Config</li> </ul> </li> <li>• Limited IP Multicast (256 profiles and 16 entries per profile)</li> </ul>
<p>Advanced Features</p>	<ul style="list-style-type: none"> <li>• Automatic Device Discovery</li> <li>• Batch Configuration</li> <li>• Batch Firmware Upgrading</li> <li>• Intelligent Network Monitoring</li> <li>• Abnormal Event Warnings</li> <li>• Unified Configuration</li> <li>• Reboot Schedule</li> </ul>
<p>VLAN</p>	<ul style="list-style-type: none"> <li>• VLAN Group             <ul style="list-style-type: none"> <li>- Max. 4K VLAN Groups</li> </ul> </li> <li>• 802.1Q tag VLAN</li> <li>• MAC VLAN</li> <li>• Protocol VLAN</li> <li>• GVRP</li> <li>• Voice VLAN</li> </ul>
<p>Access Control List</p>	<ul style="list-style-type: none"> <li>• Support up to 230 entries</li> <li>• Time-Range             <ul style="list-style-type: none"> <li>- Time Slice</li> <li>- Week Time-Range</li> <li>- Absolute Time-Range</li> <li>- Holiday</li> </ul> </li> <li>• Time-based ACL</li> <li>• MAC ACL             <ul style="list-style-type: none"> <li>- Source MAC</li> <li>- Destination MAC</li> <li>- VLAN ID</li> <li>- User Priority</li> <li>- Ether Type</li> </ul> </li> </ul>

	<ul style="list-style-type: none"> <li>• IP ACL             <ul style="list-style-type: none"> <li>- Source IP</li> <li>- Destination IP</li> <li>- IP Protocol</li> <li>- TCP Flag</li> <li>- TCP/UDP Source Port</li> <li>- TCP/UDP Destination Port</li> <li>- DSCP/IP TOS</li> </ul> </li> <li>• IPv6 ACL</li> <li>• Combined ACL</li> <li>• Rule Operation             <ul style="list-style-type: none"> <li>- Permit/Deny</li> </ul> </li> <li>• Policy Action             <ul style="list-style-type: none"> <li>- Mirror</li> <li>- Rate Limit</li> <li>- Redirect</li> <li>- QoS Remark</li> </ul> </li> <li>• ACL Rules Binding             <ul style="list-style-type: none"> <li>- Port Binding</li> <li>- VLAN Binding</li> </ul> </li> <li>• Actions for flows             <ul style="list-style-type: none"> <li>- Mirror (to supported interface)</li> <li>- Redirect (to supported interface)</li> <li>- Rate Limit</li> <li>- QoS Remark</li> </ul> </li> </ul>
<p>Security</p>	<ul style="list-style-type: none"> <li>• AAA</li> <li>• 802.1X             <ul style="list-style-type: none"> <li>- Port based authentication</li> <li>- MAC (Host) based authentication</li> <li>- Authentication Method includes PAP/EAP-MD5</li> <li>- MAB</li> <li>- Guest VLAN</li> <li>- Support Radius authentication and accountability</li> </ul> </li> <li>• IP/IPv6-MAC Binding             <ul style="list-style-type: none"> <li>- 512 Binding Entries</li> <li>- DHCP Snooping</li> <li>- DHCPv6 Snooping</li> <li>- ARP Inspection</li> <li>- ND Detection</li> </ul> </li> <li>• IP Source Guard             <ul style="list-style-type: none"> <li>- 253 Entries</li> <li>- Source IP+Source MAC</li> </ul> </li> <li>• IPv6 Source Guard</li> </ul>

	<ul style="list-style-type: none"> <li>- 183 Entries</li> <li>- Source IPv6 Address+Source MAC</li> <li>• DoS Defend</li> <li>• Static/Dynamic/Permanent Port Security</li> <li>- Up to 64 MAC addresses per port</li> <li>• Broadcast/Multicast/Unicast Storm Control</li> <li>- kbps/ratio control mode</li> <li>• Port Isolation</li> <li>• Secure web management through HTTPS with SSLv3/TLS 1.2</li> <li>• Secure Command Line Interface (CLI) management with SSHv1/SSHv2</li> <li>• IP/Port/MAC based access control</li> </ul>
IPv6	<ul style="list-style-type: none"> <li>• IPv6 Static Routing and ACL</li> <li>• IPv6 Dual IPv4/IPv6</li> <li>• IPv6 Interface</li> <li>• Multicast Listener Discovery (MLD) Snooping</li> <li>• IPv6 neighbor discovery (ND)</li> <li>• Path maximum transmission unit (MTU) discovery</li> <li>• Internet Control Message Protocol (ICMP) version 6</li> <li>• TCPv6/UDPv6</li> <li>• IPv6 applications</li> <li>- DHCPv6 Client</li> <li>- Ping6</li> <li>- Tracert6</li> <li>- Telnet(v6)</li> <li>- IPv6 SNMP</li> <li>- IPv6 SSH</li> <li>- IPv6 SSL</li> <li>- Http/Https</li> <li>- IPv6 TFTP</li> </ul>
MIBs	<ul style="list-style-type: none"> <li>• MIB II (RFC1213)</li> <li>• Bridge MIB (RFC1493)</li> <li>• P/Q-Bridge MIB (RFC2674)</li> <li>• Radius Accounting Client MIB (RFC2620)</li> <li>• Radius Authentication Client MIB (RFC2618)</li> <li>• Remote Ping, Traceroute MIB (RFC2925)</li> <li>• Support TP-Link private MIBs</li> <li>• RMON MIB(RFC1757, rmon 1,2,3,9)</li> </ul>



## MANAGEMENT

Management Features	<ul style="list-style-type: none"><li>• Web-based GUI</li><li>• Command Line Interface (CLI) through telnet</li><li>• SNMPv1/v2c/v3</li><li>• SNMP Trap/Inform</li><li>• RMON (1,2,3,9 groups)</li><li>• SDM Template</li><li>• DHCP/BOOTP Client</li><li>• Dual Image, Dual Configuration</li><li>• CPU Monitoring</li><li>• Cable Diagnostics</li><li>• EEE</li><li>• SNTP</li><li>• System Log</li></ul>
---------------------	---

## OTHERS

Environment	Operating Temperature: 0°C~40°C (32°F~104°F); Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing
Certification	CE, FCC, RoHS, ISO

[www.ewit.in](http://www.ewit.in)