



EW-C6PCS-2M

BASIC SPECIFICATIONS	
Cate 6 Patch Cord Conforming to ANSI/TIA/EIA-568 C.2 or ISO/IEC:11801 latest	Yes
Patch Cord Type: Category 6 Unshielded/Unshielded Twisted Pair or Category 6 Foiled/Unshielded Twisted Pair	CAT6 S/FTP
Type:	LSZH 1000Base T Transmission
Patch cord Colour	Blue/Red/Grey/Green/Yello
Conductor Diameter	24 to 26 AWG
Length of Patch Cord (Mtrs)	2
Applications: 0BASE-T, 100BASE-TX Fast Ethernet, 1000BASE-T (IEEE802.3), 100VG-AnyLAN (IEEE802.12), 250 MHz Broadband Video, Voice, T1, ISDN, 155/ 622 Mbps ATM, Power over Ethernet (POE, POE+, 4 PPOE)	Yes
Termination Type / Connection Type	Insulation Piercing Connection (IPC)
Modular Plug	RJ45
Plug Insertion Durability	≥ 750 mating cycles"
Conductor Material	Stranded copper
Conductor Insulation Material	Polyethylene
Cable Jacket Material	Fire retardant PVC
Storage Temperature Range	-20 deg. C to +70 deg. C
Operating Temperature Range	-20 deg. C to +70 deg. C
UL Marking on Cable	Yes