



EW-CAT PC03M

Make & Model

Make	ewit
Model	EW-CAT PC03M

GENERIC

Cate 6 patch cord conforming to ANSI/TIA/EIA-568 C.2 or ISO/IEC:11801 latest	Yes
--	-----



Patch cord type : Category 6 Unshielded/Unshielded twisted pair or Category 6 Foiled/Unshielded twisted pair	CAT6 U/UTP
Patch cord colour	Grey
Conductor diameter	24 to 26 AWG
Length of Patch cord (Mtrs)	3.0

CONSTRUCTIONAL

Applications: 0BASE-T, 100BASE-TX Fast Ethernet, 1000BASE-T (IEEE802.3) , 100VG-AnyLAN (IEEE802.12), 250 MHz Broadband Video, Voice, T1, ISDN, 155/ 622 Mbps ATM , Power over Ethernet (POE, POE+, 4 PPOE)	Yes
Termination type / Connection type	Insulation Piercing Connection (IPC)
Modular plug	RJ45
Plug insertion durability	≥ 750 mating cycles"
Conductor Materail	Stranded copper
Conductor Insulation Material	Polyethelene
Cable jacket material	Fire retardant PVC
Storage temperature range	-20 deg.C to +60 deg.C

Operating temperature range	-20 deg.C to +60 deg.C
-----------------------------	------------------------

CERTIFICATIONS

Category 6 patch cord shall have valid verified certificate in channel from ETL /3P /GHMT /Delta/Intertek /UL as per CAT 6 standards ANSI//TIA/EIA-568 C.2 latest or ISO/IEC:11801 latest	Yes
If "Yes" Certificate number - Must declare	YES
UL Marking on Cable	Yes
Availability of complete and satisfactory type test Report from Central Government / NABL/ ILAC accredited laboratory as per Governing Specification	Yes
Test report number	10261728
Report date	3.3.2018
Name and address of lab	DELHI
All the test reports shall furnish to the buyer/consignee on demand	Yes