



## EW-IP2040DVF

### IMAGE SENSOR

Image Sensor Type	CMOS
Image Sensor Size	1 inch
Camera Image Sensing capacity (Picture Mode)	2MP
Resolution	720P ( 1280 x 720 ),D1 (704 x 480 Pixel),Full HD (1920 x 1080 Pixel),HD (1280 x 720 Pixel)
Day/Night Capable	Yes
IR illumination Range(mtr)	40

### CAMERA TYPE

Type of Camera Housing	DOME CAMERA
IP Camera	Yes



PTZ Camera	No
------------	----

## OPTICS

Lens Type	Motorized Varifocal
Focal Length(mm)	2.8 - 12
Iris Control	Fixed iris
Focus Mode	Manual

## VIDEO

Frame Rate (fps)	25,30,50,60
Video Compression	H.264,H.265,H.265+,MJPEG
Video Streaming	Triple compressed stream

## PAN / TILT / ZOOM

Panning Range	NA
Pan Speed (deg/sec)	NA
Tilt Range below horizontal (deg)	NA
Tilt Range above horizontal (deg)	NA
Tilt Speed (deg/sec)	NA
Optical Zoom	NA
Digital Zoom	12X



## AUDIO

Audio Support	Yes
Audio Compression	NA
Audio Streaming	NA
Number of Audio Input Channel	NA
Number of Audio Output Channel	NA
External Microphone Support	No

## ALARM

Alarm Support	Yes
Number of Alarm Digital Input	NA
Number of Alarm Relay Output	NA
Pre/Post Alarm Buffer	No

## SECURITY

Multi Level User ID/Password	Yes
IP Address Filtering	Yes
Encrypted Data Transmission	HTTPS (SSL/TSL)

## PERFORMANCE

Minimum Illumination for Capturing Color Image	0.001 lux
Electronic Shutter Speed(sec)	1/3 to 1/10000



WDR (Wide Dynamic Range)	120 dB
SNR (Signal to Noise Ratio)	50-60
Auto Exposure	Auto Level Control, Electronic Level Control

## FEATURES

White Balance ( Indoor/Out door/Manual Selectable)	Yes
Auto Gain Control (On/Off selectable)	Yes
Back Light Compensation	Yes
Remote Administration (Remote configuration and status using web based tool)	Yes
Remote System Update Over Network	Yes
PC Client (PC application client with a channel recording feature support)	Yes
Web Client (Viewer through HTTP system configuration)	Yes
On Screen Display in English	Yes
ONVIF Support	Yes
Presets	100
Group Touring	5
Privacy Zones	4

## NETWORK AND INTERFACE

Supported Protocols	IPv6, UDP, SNMP, IGMP, DHCP, RTP, RSTP
---------------------	--



IP Support	NA
Signal Processing	Digital Signal Process
IPv6 ready	Yes
Wireless	No
Simultaneous Connections	10

## STORAGE

On Board SD Card Support	No
SD Card Memory(GB)	NA

## HOUSING

Installation Type	Indoor,Outdoor
Material of the Housing construction	Alluminium
Protection	IP67
Vandal Resistant Housing	Yes
If Yes, IK rating	IK 10
Mounting bracket	Ceiling Mounted
Weight	350 gram
Dimensions (mm x mm x mm)	-

## POWER SUPPLY

Power Input	12 V DC,PoE
Power Consumption	2.2 Watt



Suitable Adapter Shall be Supplied to Make the Equipment Work on 230 V (+/- 10 %), 50 Hz	Yes
--	-----

## OPERATING CONDITIONS

Operating Temperature Range	-30 to +50 deg C
Relative Humidity Non Condensing (%)	95

## WARRANTY / SERVICES

Warranty	3 year
Time for Replacement of Defective Product During Warranty Period	72 hour
Supply of Compatible drivers and software included	Yes

## ENVIRONMENTAL / CERTIFICATION

Availability of facility & infrastructure for verification of all parameters, features, and capability with Seller	Yes
Availability of facility to test signal to noise ratio of camera at 0-01 lux	Yes
Conformity to Dry Heat test at 55 degree C for 16 hours as per IS :9000 latest	Yes
Conformity to Damp heat at 40 degree C - 95% RH (cyclic test): two cycles of 16+8 hours as per IS: 9000 latest	Yes
Conformity to Cold test at -10 / -20 degree C for 4 hours as per IS: 9000 latest, as applicable	Yes
BIS Registration for safety general	Yes



requirements as per IS 13252 (Part 1):latest	
Availability of Type Test Report from Central Govt /NABL/ILAC accredited lab to prove conformity to specification	No
Test Report Number and Date	-
Name and Address of Test Lab	-
Certification	FCC,CE,RoHS

[www.ewit.in](http://www.ewit.in)