



EW-P04SFP

Specification: -

Type of Switch:	Unmanaged
Technology:	PoE
Network Interface:	PoE: 4 Port 10/100/1000 Mbps SFP: 2 Port 10/100/1000 Mbps
Standard Network Protocols:	IEEE802.3 10BASE-T, IEEE 802.3u 100BASE—TX, ANSI/IEEE 802.3 NWay Auto-Negotiation, IEEE802.3x Flow Control, IEEE 802.3af/at standard
Forwarding Method:	Store-and-Forward
Flow Control:	Back-Pressure Flow Control in IEEE 802.3x Full Duplex
MAC address Table:	1K QoS
Switching Capacity (Non-Blocking):	36GBPS
Packet Forwarding Rate:	10M:14,800pps, 100M: 148,800pps
Forwarding Mode:	Store-and-forward switching
Packet Buffer Memory:	4K
Throughput (MPPS):	14.88
Transmission Distance:	Up to 200 Meters
Max Power Consumption:	30W
PoE Budget:	65W
VLAN	Supports up to 4K VLANs Simultaneously (out of 4K VLAN IDs) Port/MAC/Protocol-based VLAN Management VLAN configuration
Operating Temperature:	-10°C to 40°C
Storage Temperature:	-40 ° ~ 70 ° C
Surge Protection:	6KV
Storage Humidity:	5% to 95% RH Non-Condensing
Power Input:	48V DC, 0.8 A Reverse Connection Protection
Certification:	CE, FCC, ROHS