



## Layer 2 Access Switch Rev 1

### DETAILED SPECIFICATIONS

|                                              |               |
|----------------------------------------------|---------------|
| Type of Switch                               | Managed       |
| Technology                                   | Non PoE       |
| Number of 1G Copper Ports                    | 8             |
| Number of 10G Copper Ports                   | 0             |
| Number of 1 G SFP Port (Uplink)              | 0             |
| Number of 10 G SFP+ Port (Uplink)            | 0             |
| Multi-Gigabit Support                        | No            |
| Redundant Power supply ( from day one)       | Not Available |
| Console Port                                 | Not Available |
| Switching Capacity-Non Blocking (Gbps)       | 20            |
| Throughput (MPPS)                            | 5             |
| Operating System                             | Available     |
| Dedicated Stacking Port/Slot ( from day one) | Not Available |
| Stacking Bandwidth (Gbps)                    | 1             |
| Basic Layer-3 Protocol                       | -             |
| Security Feature                             | -             |
| Management Protocol                          | -             |
| QoS                                          | -             |
| Operating Temperature Range (Degree C)       | 70            |
| Operating Humidity (RH)(%)                   | 90            |
| IPv6 Ready from day one and dully certified  | Yes           |
| PoE Power Budget ( Watt )                    | 150           |

|                      |        |
|----------------------|--------|
| On Site OEM Warranty | 1 Year |
|----------------------|--------|