



CROSS-SECTION N x S mm ²	No. of Conductors x OD(mm)	REFERECE INFORMATION			
		OD (mm)		WEIGHT (kg/km)	MAX. CONDUCTOR RESISTANCE (Ω/KM 20°C)
		MIN.	MAX.		
2x0.75	2x24/0.2	6.0	7.6	50	26
2x1.0	2x32/0.2	6.4	7.8	57.8	19.5
2x1.5	2x30/0.25	7.2	8.8	74.7	13.3
2x2.5	2x49/0.25	8.8	11.0	120	7.98
3x0.75	3x24/0.2	6.4	8.0	63.1	26.0
3x1.0	3x32/0.2	6.8	8.4	74.0	19.5
3x1.5	3x30/0.25	7.8	9.6	102.0	13.3
3x2.5	3x49/0.25	9.6	11.5	162.0	7.98
4x0.75	4x24/0.2	7.0	8.6	78.5	26.0
4x1.0	4x32/0.2	7.6	9.2	97.2	19.5
4x1.5	4x30/0.25	8.8	11.0	133.0	13.3
4x2.5	4x49/0.25	10.5	12.5	204.0	7.98
5x0.75	5x24/0.2	7.8	9.4	96.9	26
5x1.0	5x32/0.2	8.2	11.0	115	19.5
5x1.5	5x30/0.25	9.8	12.0	158	13.3
5x2.5	5x49/0.25	11.5	14.0	249	7.98